

## IDEATECH READY MADE VFD PANEL PRICE LIST STANDARD DISCOUNT 50%

SR NO.	KW	APPROX HP	DRIVE RATED CURRENT	MAX CURRENT FOR 1 MINUTE	GENERAL APPROX CURRENT AS PER HP	VFD BRAND	VFD MODEL	FRAME	MCB OR MCCB AMP	L&T OR SCHNEIDER MCCB MCB OR MCCB TM TYPE	GENERAL ACC	PANEL LP	FOR COPPER BUSBAR RS EXTRA 2A FOR 1 SQMM AREA OF BUSBAR
1	0.75	1.0	2.1	3.2	1.5	INOVANCE	MD310	FRAME 1	6	MCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, POTENTIOMETER 10 TURN (POT 10 TURN)	36375	NO BUSBAR
2	1.5	2.0	3.8	5.7	3.0	INOVANCE	MD310	FRAME 1	6	MCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, POTENTIOMETER 10 TURN (POT 10 TURN)	37590	NO BUSBAR
3	2.2	3.0	5.1	7.7	4.5	INOVANCE	MD310	FRAME 1	6	MCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, POTENTIOMETER 10 TURN (POT 10 TURN)	39345	NO BUSBAR
4	3.7	5.0	9.0	13.5	7.5	INOVANCE	MD310	FRAME 2	10	MCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, POTENTIOMETER 10 TURN (POT 10 TURN) 50 VA TRANSFORMER	48447	NO BUSBAR
5	5.5	7.5	13.0	19.5	11.3	INOVANCE	MD310	FRAME 2	16	MCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, POTENTIOMETER 10 TURN (POT 10 TURN) 50 VA TRANSFORMER	60552	NO BUSBAR
6	7.5	10.0	17.0	25.5	15.0	INOVANCE	MD310	FRAME 3	16	MCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, POTENTIOMETER 10 TURN (POT 10 TURN) 50 VA TRANSFORMER	67050	NO BUSBAR
7	11	15.0	25.0	37.5	22.5	INOVANCE	MD310	FRAME 3	25	MCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, POTENTIOMETER 10 TURN (POT 10 TURN) 50 VA TRANSFORMER	86220	NO BUSBAR
8	15	20.0	32.0	48.0	30.0	INOVANCE	MD310	FRAME 4	32	MCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 100 VA TRANSFORMER, POTENTIOMETER 10 TURN (POT 10 TURN)	98840	NO BUSBAR
9	18.5	25.0	37.5	56.3	37.5	INOVANCE	MD290	FRAME 5	40	MCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 100 VA TRANSFORMER, 24 VOLT 5A SMPS, POTENTIOMETER 10 TURN (POT 10 TURN)	127888	NO BUSBAR
10	22	30.0	45.0	67.5	45.0	INOVANCE	MD290	FRAME 5	50	MCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 100 VA TRANSFORMER, 24 VOLT 5A SMPS, POTENTIOMETER 10 TURN (POT 10 TURN)	133018	NO BUSBAR
11	30	40.0	60.0	90.0	60.0	INOVANCE	MD290	FRAME 6	63	MCCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 100 VA TRANSFORMER, 24 VOLT 5A SMPS, POTENTIOMETER 10 TURN (POT 10 TURN)	176228	NO BUSBAR
12	37	50.0	75.0	112.5	75.0	INOVANCE	MD290	FRAME 6	80	MCCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 100 VA TRANSFORMER, 24 VOLT 5A SMPS, POTENTIOMETER 10 TURN (POT 10 TURN)	204600	NO BUSBAR
13	45	60.0	91.0	136.5	90.0	INOVANCE	MD290	FRAME 7	100	MCCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA TRANSFORMER, 24 VOLT 5A SMPS, POTENTIOMETER 10 TURN (POT 10 TURN)	252377	1304
14	55	75.0	112.0	168.0	112.5	INOVANCE	MD290	FRAME 7	125	MCCB 10 KA BRAEKING CAPACITY	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA TRANSFORMER, 24 VOLT 5A SMPS, POTENTIOMETER 10 TURN (POT 10 TURN)	290643	1630

15	75	100.0	150.0	225.0	150.0	INOVANCE	MD290	FRAME 8	160	MCCB BREAKING CAPACITY 25 OR 36 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	400576	2174
16	90	120.0	176.0	264.0	180.0	INOVANCE	MD290	FRAME 8	200	MCCB BREAKING CAPACITY 25 OR 36 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	473681	2608
17	110	150.0	210.0	315.0	225.0	INOVANCE	MD290	FRAME 9	250	MCCB BREAKING CAPACITY 25 OR 36 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	537202	3260
18	132	180.0	253.0	379.5	270.0	INOVANCE	MD290	FRAME 9	320	MCCB BREAKING CAPACITY 25 OR 36 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	661397	3912
19	160	215.0	304.0	456.0	322.5	INOVANCE	MD290	FRAME 9	320	MCCB BREAKING CAPACITY 25 OR 36 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	755419	4673
20	200	270.0	377.0	565.5	405.0	INOVANCE	MD290	FRAME 10	400	MCCB BREAKING CAPACITY 25 OR 36 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	1052065	5868
21	220	300.0	424.0	636.0	450.0	INOVANCE	MD290	FRAME 10	500	MCCB BREAKING CAPACITY 25 OR 36 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	1176136	6521
22	250	335.0	465.0	697.5	502.5	INOVANCE	MD290	FRAME 11	500	MCCB BREAKING CAPACITY 25 OR 36 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	1479511	7281
23	280	370.0	520.0	780.0	555.0	INOVANCE	MD290	FRAME 11	630	MCCB BREAKING CAPACITY 25 OR 36 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	1673972	8042
24	315	425.0	585.0	877.5	637.5	INOVANCE	MD290	FRAME 12	630	MCCB BREAKING CAPACITY 25 OR 36 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	1841476	9237
25	355	475.0	650.0	975.0	712.5	INOVANCE	MD290	FRAME 12	800	MCCB BREAKING CAPACITY 36 OR 50 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	1998208	10324
26	400	530.0	725.0	1087.5	795.0	INOVANCE	MD290	FRAME 12	800	MCCB BREAKING CAPACITY 36 OR 50 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	2416785	11520
27	450	600.0	820.0	1230.0	900.0	INOVANCE	MD290	FRAME 12	1000	MCCB BREAKING CAPACITY 36 OR 50 KA WITH HANDLE & SPERADER	1) RYB INDICATOR 3 NOS. 2) ON TRIP INDICATOR 3) FORWARD, REVERSE, STOP PUSHBUTTON, JOG FORWARD JOG REVERSE PUSHBUTTON, 15 CONNECTOR APPROX FROM DRIVE TO PANEL BOTTOM TERMINAL PART, RS 485 COMM, 350 VA VA TRANSFORMER, 24 VOLT 5A SMPS, VAF METER, 3 CTCOIL INPUT, MOTOR RPM METER, POTENTIOMETER 10 TURN (POT 10 TURN)	2585697	13041